
6/19/1 (Item 1 from file: 345)

12480577

Basic Patent (No,Kind,Date): JP 7149950 A2 950613

PATENT FAMILY:

JAPAN (JP)

Patent (No,Kind,Date): JP 7149950 A2 950613

RUBBER COMPOSITION FOR TIRE TREAD (English)

Patent Assignee: BRIDGESTONE CORP

Author (Inventor): KIMURA SHIGEO; YAGAWA KAZUO; HASHIMOTO TAKATSUGU;

AKAISHI KOJI; HATTORI KENICHI

Priority (No,Kind,Date): JP 93298313 A 931129

Applic (No,Kind,Date): JP 93298313 A 931129

IPC: * C08L-007/00; B60C-001/00; C08K-003/04; C08L-009/00

CA Abstract No: ; 123(24)316655S

Derwent WPI Acc No: ; C 95-243724

Language of Document: Japanese

Inpadoc/Fam.& Legal Stat (Dialog® File 345): (c) 2001 EPO. All rights reserved.

6/19/2 (Item 1 from file: 347)

04857350 RUBBER COMPOSITION FOR TIRE TREAD

Pub. No.: 07-149950 [JP 7149950 A]

Published: June 13, 1995 (19950613)

Inventor: KIMURA SHIGEO

YAGAWA KAZUO

HASHIMOTO TAKATSUGU

AKAISHI KOJI

HATTORI KENICHI

Applicant: BRIDGESTONE CORP [000527] (A Japanese Company or Corporation), JP (Japan)

Application No.: 05-298313 [JP 93298313]

Filed: November 29, 1993 (19931129)

International Class: [6] C08L-007/00; B60C-001/00; C08K-003/04; C08L-009/00

JAPIO Class: 14.2 (ORGANIC CHEMISTRY -- High Polymer Molecular Compounds); 26.2 (TRANSPORTATION -- Motor Vehicles)

ABSTRACT

PURPOSE: To produce the composition which can give a tire tread improved in wet skid resistance without detriment to processability, wear resistance and low heat buildup.

CONSTITUTION: The composition is prepared by compounding 100 pts.wt. natural rubber and/or synthetic diene rubber with 5-30 pts.wt. at least one powder of an inorganic compound represented by the general formula: $M_xSiO_2 \cdot yH_2O$ (wherein M is at least one oxide or hydroxide of a metal selected from among Al, Mg, Ti and Ca; and x and y are each an integer of 0-10) and having a particle diameter of 10.μm or below, and 30-100 pts.wt. carbon black.